

StarLine

Designed by BÖWE



PX16
PX19



THE NEW STANDARD

StarLine

Designed by BÖWE

BÖWE
Textile Cleaning

RELIABLE DRYCLEANING MACHINES THROUGH PROVEN BÖWE QUALITY

PATENTED – DYNAMIC CAGE PERFORATION

Optimum cleaning results can only be achieved through a high-performance drying system in your drycleaning machine. BÖWE utilize a patented dynamic cage perforation, which allows for a considerably better penetration of the



Best possible drying by optimized cage airflow

garments with drying air and results in an effective, fast drying even with delicate garments; this BÖWE developed cage perforation has been used in the PremiumLine series for years. Together with the optimized program sequences, with considerably reduced cycle times, BÖWE StarLine machines offer strong capacity at an economically advantageous price.



Proven principle: Only one opening for button trap and lint filter on PX models



AN IMPORTANT POINT - MAINTENANCE

Thanks to the ideal combination of button trap and lint filter in one place maintenance of this machine is reduced to a minimum. Because of the large filter surface and button trap basket, cleaning is sufficient only once a day in standard operation.

Another environmentally friendly feature of the StarLine is the emission free still rake out system. Using an azeotropic compound of water and perc from a reduction of the boiling point, means this is a minimal maintenance constructed unit.



The automatic emission free still rake out system requires no manual intervention in normal operation

YOUR ADVANTAGE - BÖWE'S STRENGTH IN TECHNOLOGY, KNOW-HOW AND PRODUCTION

YOUR ADDED VALUE AT A GLANCE

- Satisfied customers by optimum standard cleaning programs geared to any kind of garments
- Greatest flexibility for the drycleaner by freely programmable cleaning programs
- Optimum drying and shorter cycle times by patented dynamic cage perforation
- Greatest possible safety by a well-engineered diagnostic system and operator guidance
- Optimum solvent quality by modern distillation management
- Less loss of solvent by post water separator and emission free still rake out system
- Best garment quality by spraying unit with rinsing pipe
- Easy, time saving maintenance

		PX16	PX19
Solvent		perchloroethylene	perchloroethylene
Cage			
Loading capacity	kg (1:20)	15	18
	kg (1:19)	16	19
Cage volume	l	300	360
Cage diameter	mm	820	820
Cage depth	mm	570	680
Cleaning speed	rpm	40	40
Maximum extraction speed	rpm	400	400
Tanks (filling quantities)			
Tank I	l	145	170
Tank II	l	95	110
Still			
Filling volume	l	120	120
Extraction filter			
Filter surface	sqm	2.4	2.4
Filter contents	l	40	40
Machine dimensions			
Width	mm	1,840	1,840
Depth	mm	1,390	1,500
Height (entry measurement)	mm	1,995	1,995
Height (installed)	mm	2,260	2,260
Weight			
Without solvent	kg	1,180	1,280
Floor surface	sqm	2.5	2.6

Subject to technical changes and error.



MAXIMUM DEMANDS ON QUALITY AND SAFETY

In the drycleaning business protection of both man and environment is of great importance to us. By use of the SLIMSORBA integrated adsorption unit (if desired) especially low residual solvent concentrations in the garments are reached - an advantage as regards freshness and well-being for your customers and employees.

For highest quality demands BÖWE offers a dosing unit as standard on the StarLine machines. Optionally, you can add another dosing unit and a spraying unit for finishing of high-quality garments.



SLIMSORBA to meet strictest environmental regulations and for best working conditions



The spraying unit (optional) with rinsing pipe for finishing directly off the drum



CREATIVE THINKING, QUALITY AND CUSTOMER SATISFACTION GOVERN BÖWE'S BUSINESS PHILOSOPHY. INNOVATION - THE KEY TO SUCCESS.

Tradition meets innovation - for more than 60 years BÖWE has been one of the leading companies in the field of drycleaning machinery. As a pioneer of cleaning technology we major on this tradition, on responsibility and comprehensive know-how. We offer modern and innovative drycleaning machinery for perc and HC, and also for the new silicone-based alternatives. No matter what solvent - our machines support your success through cost effectiveness and best cleaning results. Our quality standards work from the

inside out, i.e. from development through to after sales support and service.

We at BÖWE think of proximity to customers in two ways. On the one hand, from a geographical perspective: besides our company factory base in Augsburg, Germany, sales and service partners in more than 50 countries guarantee BÖWE's presence in all important markets on all continents.

On the other hand, proximity to customers means fast delivery and perfect after sales support. This alone, however, is not sufficient to us. Since we can only fulfill international demands and act totally customer-effectively through consultation even in the development phase we discuss, design and modify together with our international partners in order to consider the local requirements of all markets.

PX16 PX19



BÖWE Textile Cleaning GmbH
Rumplerstrasse 2 · D-86159 Augsburg
Phone: + 49 (0) 821 5707-0
Telefax: + 49 (0) 821 5707-200
trade@boewe-tc.de · www.boewe-tc.de

Your BÖWE Partner

BÖWE
Textile Cleaning